

PLATE EXTRUSION LINE

Specifications:

Price	Contact us	
Brand Name	JIKE	
Model Number	SJBP-1000 SJBP-1400	
Place of Origin	Jiangsu, China	
Min.Order Quantity	1 SET	
Payment Terms	T/T,L/C,D/P West Union	
Delivery Detail	10-25 Days	

Detail Introduction:

Product Description

The lines have the advantages of well-planned layout, cimpact in structure, fine in performance such as homogenous plasticization, high output and long service life. The screws optimized. Exchanging screen rapidly about 1.5 seconds every cutting unit can guarantee the precise measurements through the adjustment of length and width, the error of product's diagonal<3mm, the using rage of products is wide. The line can adopt one ,two, three extruders together to do one layer, many layers plastic sheet ,The electric control system utilize imported frequency converter, it's safe and reliable, The lines are suit for PP,PE,PC,ABS,PVC,PMMA,PET,HTPS and etc. raw materials.

Main technical Parameter

Model	SJBP-1000	SJBP-1400
Screw diameter of extruder(mm)	?90	?100
Speed of screw(r.p.m)	0~110	0~100
Yield(kg/h)	180	300
Linear velocity (m/min)	0.2~6	0.2~6
Total power(kw)	138	190
Width of product(mm)	850	1250
Weight of whole machine (t)	10	15
Overall dimensions (mm)	10000*3200*2000	30000*3600*2500

Note: The requirements for different products, other types covering this. Form and technical data are subject to change without notice.