

PLATE EXTRUSION LINE

Specifications :

| | |
|--------------------|------------------------|
| Price | Contact us |
| Brand Name | JIKE |
| Model Number | SJBP-1000 SJBP-1400 |
| Place of Origin | Jiangsu, China |
| Min.Order Quantity | 1 SET |
| Payment Terms | T/T,L/C,D/P West Union |
| Delivery Detail | 10-25 Days |

Detail Introduction :

Product Description

The lines have the advantages of well-planned layout, compact in structure, fine in performance such as homogenous plasticization, high output and long service life. The screws optimized. Exchanging screen rapidly about 1.5 seconds every cutting unit can guarantee the precise measurements through the adjustment of length and width, the error of product's diagonal < 3mm, the using range of products is wide. The line can adopt one, two, three extruders together to do one layer, many layers plastic sheet, The electric control system utilize imported frequency converter, it's safe and reliable, The lines are suit for PP, PE, PC, ABS, PVC, PMMA, PET, HTPS and etc. raw materials.

Main technical Parameter

| Model | SJBP-1000 | SJBP-1400 |
|--------------------------------|-----------------|-----------------|
| Screw diameter of extruder(mm) | 90 | 100 |
| Speed of screw(r.p.m) | 0~110 | 0~100 |
| Yield(kg/h) | 180 | 300 |
| Linear velocity (m/min) | 0.2~6 | 0.2~6 |
| Total power(kw) | 138 | 190 |
| Width of product(mm) | 850 | 1250 |
| Weight of whole machine (t) | 10 | 15 |
| Overall dimensions (mm) | 10000*3200*2000 | 30000*3600*2500 |

Note: The requirements for different products, other types covering this.

Form and technical data are subject to change without notice.