

# PVC CLING FILM BLOWN LINE (THE ONLY DOMESTIC MANUFACTURER)

## Specifications :

Price	Contact us
Brand Name	JIKE
Model Number	2800
Place of Origin	Jiangsu, China
Min.Order Quantity	1 SET
Payment Terms	T/T,L/C,D/P West Union
Delivery Detail	10-25 Days

## Detail Introduction :

### Product Description

This production line manufactures PVC film by blowing method. It has three characters:

1. The diaphragm is thin. And its minimum is up to 0.006mm.
2. The coil diameter is big. Each is between 6000m-9000m. Suitable for plant using packaging and split charging.
3. High yield.

### High quality

High performance ( film thickness: 0.006mm-0.011mm,

film length: 6000m-9000m )

High capacity ( more than 400kg / h )

Low loss (all scrap recycling)

## Main technical parameters

<b>Model</b>	<b>2800</b>
Screw Diameter (mm)	φ120
L/D Ratio of Screw	28:1
Rotation die orifice diameter (mm)	φ250
Width of Finished Film (mm)	2300×2
Thickness of Finished Film (mm)	0.006-0.010
Max. Extrusion Capacity (kg/h)	450
Design Line Speed (m/min)	160
Total Installed Power (kw)	300
Overall Dimensions(L×W×H) (m)	30×8×13
Weight (T)	85

The above technical data will be changed without noticed.