

PVC CLING FILM BLOWN LINE (THE ONLY DOMESTIC MANUFACTURER)

Specifications :

Price	Contact us
Brand Name	JIKE
Model Number	2800
Place of Origin	Jiangsu, China
Min.Order Quantity	1 SET
Payment Terms	T/T,L/C,D/P West Union
Delivery Detail	10-25 Days

Detail Introduction :

Product Description

This production line manufactures PVC film by blowing method.It has three characters:

- 1.The diaphragm is thin . And its minimum is up to 0.006mm.
- 2.The coil diameter is big. Each is between 6000m-9000m.Suitable for plant using packaging and split charging.
- 3.High yield.

High quality

High performance (film thickness: 0.006mm-0.011mm,

film length:6000m-9000m)

High capacity (more than 400kg / h)

Low loss(all scrap recycling)

Main technical parameters

Model	2800
Screw Diameter (mm)	?120
L/D Ratio of Screw	28:1
Rotation die orifice diameter (mm)	?250
Width of Finished Film (mm)	2300x2
Thickness of Finished Film (mm)	0.006-0.010
Max.Extrusion Capacity (kg/h)	450
Design Line Speed (m/min)	160
Total Installed Power (kw)	300
Overall Dimensions(LxWxH) (m)	30x8x13
Weight (T)	85

The above technical data will be changed without noticed.