

PVC CLING WRAP FILM PRODUCTION LINE

Specifications :

Price	Contact us
Brand Name	JIKE
Model Number	2300
Place of Origin	Jiangsu, China
Min.Order Quantity	1 SET
Payment Terms	T/T,L/C,D/P West Union
Delivery Detail	10-25 Days

Detail Introduction :

Product Description

The production line used PVC resin powder as main material, and mixed kinds of auxiliary materials. After stirring enough, produce a self-adhesive PVC cling wrap film by extruder. The film has a high tensile strength, good performance of the droplet, a high degree of transparency, good surface luster performance. Packaged goods not only beautiful, but also to keep the food fresh for a long time. Widely used in supermarkets, hotels, restaurants, bakeries and family occasions, vegetables, cold dishes, fruit, meat and other product package and storage.

Main technical parameters

Model	2300
Screw Diameter (mm)	115
L/D Ratio of Screw	28:1
Width of Die (mm)	2300
Width of Finished Film (mm)	1800 (300×6 rolls)
Thickness of Finished Film (mm)	0.009-0.011
Max.Extrusion Capacity (kg/h)	300
Design Line Speed (m/min)	220
Total Installed Power (kw)	300
Overall Dimensions(L×W×H) (m)	15×5×4.5
Weight (T)	35

The above technical data will be changed without noticed.