SJ-FMZ WIDE SERIES COMPOUND FILM MACHINE

Specifications :

Price	Contact us
Brand Name	JIKE
Model Number	SJ-FMZ
Place of Origin	Jiangsu, China
Min.Order Quantity	1 SET
Payment Terms	T/T,L/C,D/P West Union
Delivery Detail	10-25 Days

Detail Introduction :

Product Description

The machine uesd PE or PP as material to compound with plastic woven cloth, widly used in wide tarpaulin geotextile, paper, woven colth and so on. Hanging extruder, walking stability and reasonable structure. With high-precision adjustment mold. Composite system with a hydraulic device, big pressure, stable and reliable. Rewinding system uses shaftless unwinding ,lock cylinder, suitable for small-bore tube, and unwingding system used the rolling friction with pneumatic cross-cutting knife, coiling formation. The operating control system using imported components, reliable quality and stable operation. The touchscreen display, a variety of data clearly, intuitive and simple to operate.

Main technical parameters

Model	SJ120-FMZ2800	SJ130-FMZ3200	SJ150-FMZ4200
Model (mm)	1600-2600	2000-3000	3000-4000
Compound thickness (mm)	0.02-0.06	0.02-0.06	0.02-0.06
Compound linear velocity (m/min)	30-80	30-80	30-80
Screw Diameter (mm)×L/D Ratio of Screw	?120x33	?130x33	?150x33
Width of die aperture (mm)	2800	3200	4200
Maximum diameter of unwinding and rewinding ?mm?	?1200	?1200	?1200
Total Installed Power (kw)	215	240	286
Overall Dimensions(L×W×H) (m)	10x12x3.5	11x12x3.5	11X15X3.2
Weight (T)	28	32	40

The above technical data will be changed without noticed.